



TQX.11001 Triple QX Motor Oil 5W-40 SYNPLUS

Document version: 8 Sep 2026



According to the specifications of

ACEA A3/B4
API CF / SN
BMW Longlife-01
Fiat 9.55535-M2 / 9.55535-N2
GM LL-B-025
MB 226.5 / 229.1 / 229.3 / 229.5
Porsche A40
Renault RN 0700 / RN 0710
VW 501.01 / 502.00 / 505.00 / 505.01

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521776032	1 L	12	-
TQX.521776031	5 L	4	-
TQX.521776035	20 L	1	-
TQX.521776039	60 L	1	-
TQX.521770066	199 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.852 kg/l	ASTM D4052
Kinematic Viscosity at 40°C	80.0 mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	13.8 mm ² /s	ASTM D445
Viscosity Index	178	ASTM D2270
Flashpoint	222 °C	ASTM D92
Pourpoint	-42 °C	ASTM D6892
Total Base Number	10.1 mgKOH/g	ASTM D2896
Sulphated Ash	1.1 mass%	ASTM D874